


Data Structures

CH4 Linked Lists

Prof. Ren-Shuo Liu

NTHU EE

Spring 2018





Outline

- 4.1-4.3 Basic singly linked lists and chains
- 4.4-4.5 Circular lists
- 4.6-4.9 Linked stacks, queues, polynomials, and sparse matrices
- 4.10 Doubly linked lists
- 4.11 Generalized lists



Sequential Representation of a List

- Insertion and deletion of arbitrary elements cause excessive data movement

list of three-letter
words ending in AT


0	BAT
1	CAT
2	EAT
3	FAT
4	HAT
5	JAT
6	

Move
data

0	BAT
1	CAT
2	
3	EAT
4	FAT
5	HAT
6	JAT

0	BAT
1	CAT
2	DAT
3	EAT
4	FAT
5	HAT
6	JAT

Insert "DAT"



Linked Representation of a List

- Insertion and deletion of arbitrary elements are simplified


Index denoting
the next element

0	BAT	1
1	CAT	2
2	EAT	3
3	FAT	4
4	HAT	5
5	JAT	0
6		

0	BAT	1
1	CAT	2
2	EAT	3
3	FAT	4
4	HAT	5
5	JAT	0
6	DAT	



0	BAT	1
1	CAT	6
2	EAT	3
3	FAT	4
4	HAT	5
5	JAT	0
6	DAT	2

Adjust
indices




Singly Linked List (Chain)

- Insertion




Chain of Three-Letter Words (Composite Class Style)




```
class ThreeLetterNode;  
// forward declaration
```

```
class ThreeLetterChain {  
public:  
    // chain manipulation operations  
    ...  
private:  
    ThreeLetterNode *first;  
};
```


```
class ThreeLetterNode {  
friend class ThreeLetterChain;  
private:  
    char data[3];  
    ThreeLetterNode *link;  
};
```



Chain of Three-Letter Words (Nested Class Style)




```
class ThreeLetterChain {  
public:  
    // chain manipulation operations  
    ...  
private:  
  
    class ThreeLetterNode {  
public:  
    char data[3];  
    ThreeLetterNode *link;  
};  
  
ThreeLetterNode *first;  
};
```






Pointer Manipulation Example

```
ThreeLetterNode * x;  
ThreeLetterNode * y;  
x = new ThreeLetterNode;  
y = new ThreeLetterNode;  
  
y->data[0] = 'B';  
y->data[1] = 'A';  
y->data[2] = 'T';  
y->link = x;  
  
*x = *y;  
  
x = y;  
  
x = y->link;  
delete x;  
delete y;
```





Chain of Integers in C++

```
class ChainNode; // forward declaration
class Chain
{
public:
    // chain manipulation operations
    ...
private:
    ChainNode *first;
}

class ChainNode {
friend class Chain;
public:
    ChainNode (int element = 0, ChainNode* next = 0)
        {data = element; link = next;}
private:
    int data;
    ChainNode *link;
};
```




Chain Manipulation Operations

- Example: create a chain with two nodes

```
void Chain::func1()
{
    // create and set fields of second node
    ChainNode* second = new ChainNode(20, 0);

    // create and set fields of first node
    first = new ChainNode(10, second);
}
```






Chain Manipulation Operations

- Insert a node with value 50


```
void Chain::func2(ChainNode* x)
{
    if(first == 0) // insert into an empty chain
        first = new ChainNode(50);
    else           // x is the inserting point
        x->link = new ChainNode(50, x->link);
}
```

first



empty case

first



non-empty case




Chain Manipulation Operations

- Delete/remove a node

```
void Chain::Delete(ChainNode* todel, ChainNode* prev)
{
    if(todel == first)
        first = first->link;
    else
        prev->link = todel->link;
    delete todel;
}
```


first



deleting first case

prev

todel




deleting others case



Template Class Chain

- It is a waste of time for programmers to develop different types of chains and their associated algorithms over and over
 - Three-letter word chain
 - Integer chain
 - ...
- It is desirable for programmers to have a **reusable chain class**
 - Template and iterators can help



Template Class Chain

```
template <class T> class ChainNode; // forward declaration
template <class T>
class Chain {
public:
    Chain( ) {first = 0;} // constructor
    // Chain manipulation operations
    .
    .
private:
    ChainNode<T>* first;
};

template <class T>
class ChainNode {
friend class Chain <T>;
private:
    T data;
    ChainNode<T>* link;
};
```

Usage:

```
Chain<int> i_list;
Chain<float> f_list;
Chain<Rectangle> r_list;
...
```



Motivation of Chain Iterators

- Consider the following tasks for a container containing integers
 - Print out all integers
 - Find the `max`, `min`, `median`, or `mean` of all integers
 - Find the `sum`, `product`, or `sum of squares` of all integers
 - Find an integer that `maximizes` a function
- All these require us to **examine all elements** of the container



Motivation of Chain Iterators

- Basic method to print out all elements

```
1 for each item in C // C is a container
2 {
3     k = current item of C;
4     cout << k
5 }
```

- First drawback of the naïve approach:
implementation is container-dependent

- For an array

```
1 for(int i = 0; i < n; i++)
3   k = a[i];
```

- For a list

```
1 for(ChainNode<int>* ptr = first; ptr != 0; ptr = ptr->link)
3   k = ptr->data;
```



Motivation of Chain Iterators

- Second drawback of the naïve approach : operations need to be member functions as they access private data
 - However, not all operations are meaningful for all classes
 - e.g., sum is meaningful for `Chain<int>` but not for `Chain<Rectangle>`
 - Number of member functions can become large
 - Infeasible for the class designer to predict all the operations
 - Class users have to learn how the container class is implemented when they want to add member function




C++ Iterators


- Object type that mimics pointers
- Typically, a nested class of a container class
- Designed to systematically access the elements of a container class one by one
- User can employ iterators to implement their own functions
- Design philosophy
 - Implementing iterators is tedious for designers
 - Users' jobs are simplified



C++ Iterators

- Support pointer-like operations
 - Using operator overloading
- Iterators are classified into five categories according to the supported operations
 - All categories support `==`, `!=`, and `*` (dereferencing)
 - **Input iterators**: support `read` access to the elements pointed at and `++`
 - **Output iterators**: support `write` access to the elements pointed at and `++`
 - **Forward iterators**: support **both input and output**
 - **Bidirectional iterators**: additionally support `--`
 - **Random access iterators**: additionally support jumps by `arbitrary` amounts





Use of Iterators

- Print-out function for a chain of integers

```
for(Chain<int>::Iterator i = C.begin(); i!=C.end(); i++)  
{  
    k = *i;  
    cout << k;  
}
```

- Traverse chain nodes by **incrementing an iterator**
- Access chain nodes through **dereferencing**
- Users do not need to directly handle chain operations



Combine Iterators with Template

- Generic print-out function for any container with iterators

```
template <class T>    // T is an iterator type
void print(T begin, T end)
{
    while(begin != end) {
        cout << *begin;
        begin++;
    }
}
```

- Similar to STL `sort()` and `find()`, which are also generic functions
- Iterators enable us to **decouple the algorithms from containers**




Chain Operations

- Design philosophy for choosing which operations to include in an object
 - Provide enough operations so that the class can be used in many applications
 - Not to include too many operations
 - Class becomes bulky and hard to understand
- Example for a chain object
 - Inserting at the back of a list
 - Concatenating two chains
 - Reversing a chain




Inserting at the Back of a List

```
template <class T>
void Chain<T>::InsertBack(const T& e)
{
    if (first) { // nonempty chain
        let last points to the last node
        last->link = new ChainNode<T>(e);
    }
    else first = new ChainNode<T>(e);
}
```



Concatenating Two Chains

```
template <class T>
void Chain <T>::Concatenate(Chain<T>& b)
{
    if (first) { // *this is nonempty
        let last point to the last node
        last->link = b.first;
    }else{
        first = b.first;
    }
    b.first = 0;
}
```




Reversing a Chain

```
template <class T>
void Chain<T>::Reverse()
{
    ChainNode<T> *curr = first,
    ChainNode<T> *prev = 0;
    ChainNode<T> *r = 0;
    while (curr) {
        r = prev;           // r trails prev
        prev = curr;        // prev trails curr
        curr = curr->link; // curr moves to the next
        prev->link = r;    // link prev to r
    }
    first = prev;
}
```


The code illustrates the process of reversing a linked list. It uses three pointers: `curr`, `prev`, and `r`. The algorithm follows these steps:

- initializing:** Initialize `curr` to `first` and `prev` to `0`.
- advancing:** Inside the loop, `r` is set to `prev`, `prev` is set to `curr`, and `curr` is moved to its next node (`curr = curr->link`).
- re-linking:** The link between `prev` and `curr` is reversed (`prev->link = r`).
- finalizing:** After the loop exits, `first` is updated to point to `prev`.




Illustrating Reversing a Chain


Initializing




Advancing




Re-linking






Illustrating Reversing a Chain


Advancing



Re-linking




Advancing
+ re-linking






Illustrating Reversing a Chain


Advancing
+ re-linking



Advancing
+ re-linking



Finalizing





Outline

- 4.1-4.3 Basic singly linked lists and chains
- **4.4-4.5 Circular lists**
- 4.6-4.7 Linked stacks, queues, polynomials, and sparse matrices
- 4.10 Doubly linked lists
- 4.11 Generalized lists




Several Variants of Linked Lists

- Circular list
 - Access pointer pointing to the **first** node
 - Access pointer pointing to the **last** node
- Circular list with a **header** nodes
- Circular list with an **available** pool




Circular Lists

- Link the last node with the first node



- Advantages
 - Capability of traversing a list with only a pointer pointing to a node in the list
 - Easy to rotate a list
- Potential disadvantages (can be solved)
 - Inserting a node becomes less efficient




Insert at the Front


- If (`first == 0`) // empty list

$\Theta(1)$ time

`first` 0




- ① `tmp = new node`
- ② `tmp->link = tmp`
- ③ `first = tmp`



Insert at the Front

- If (first != 0) // non-empty list

$\Theta(n)$ time



- ① `tmp1 = new node`
- ② traverse the whole list ($\Theta(n)$) to let `tmp2` point to the last node.

- ③ `tmp1->link = first`
- ④ `tmp2->link = tmp1`
- ⑤ `first = tmp1`



Quick Summary

- Drawback of circular lists with only an access pointer pointing to the **first** node
 - Inserting at the front becomes inefficient
 - Last node is involved
 - Time complexity is $O(n)$
 - Worse than the original non-circular lists
- Solution
 - Let access pointer point to the last node
 - By doing so, inserting at the front consumes constant time




Insert at the Front


- If (`last == 0`) // empty list

$\Theta(1)$ time

`last` 0




- ① `tmp = new node`
- ② `tmp->link = tmp`
- ③ `last = tmp`



Insert at the Front

- If($\text{last} \neq 0$)



$\Theta(1)$ time





Lists with a Header Node


- Improve data structure regularity
- Avoid special case handling
 - No need to check whether the access pointer is zero
 - Same insertion procedure for both empty and non-empty lists
- Data field of the header node can be left unused or store information about the list (if appropriate)






Insert at the Front

$\Theta(1)$ time





- ① `tmp = new node`
- ② `tmp->link = head->link`
- ③ `head->link = tmp`




Insert at the Front

$\Theta(1)$ time




- ① `tmp = new node`
- ② `tmp->link = head->link`
- ③ `head->link = tmp`




Lists with an Available Node Pool

- Use a pointer to hold pre-allocated and freed nodes
 - The pointer is shared by all the objects of the same class (i.e., the pointer is a **static** class member)
 - Expose `GetNode()` and `RetNode()` instead of **new** and **delete** (or one can overload **new** and **delete**)
 - Original **new** and **delete** are used only when necessary
- Benefits
 - Reduces frequent **new** and **delete**, which are costly operations
 - Chain can be deleted in $O(1)$ time
 - Deleting an original chain is of $O(n)$ time




Available Space Lists






Available Space Lists






Available Space Lists






Getting a Node

```
template <class T>
ChainNode<T>* CircularList<T>::GetNode()
{ // Provide a node for use
    ChainNode<T>* x;
    if (av){
        x = av;
        av = av->link;
    }else{ // out of available nodes
        x = new ChainNode<T>;
    }
    return x;
}
```







Returning a Node

```
template <class T>
void CircularList<T>::RetNode(ChainNode<T>*& x)
{// Free the node pointed to by x
    x->link = av;
    av = x;
    x = 0;
}
```

reference to
a pointer


x is cleared after being returned.
This could prevent a freed node
from still being used.





Clearing a List

```
template <class T>
void CircularList<T>::~CircularList()
{// Delete/clear the circular list
    if(last) {
        ChainNode<T>* x = last->link;
        last->link = av; // last node linked to av
        av = x;
        // first node of list becomes front of av list
        last = 0;
    }
}
```





Quick Summary

- Different list implementations have their pros and cons
 - No one-size-fit-all solution
 - No best solution
- Even the vanilla (singly, non-circular) list implementation has its suitable use
 - E.g., managing the available nodes of the available-space lists
 - Usage scenarios in which a list is usually get inserted and deleted at the front and seldom traversed



Outline


- 4.1-4.3 Basic singly linked lists and chains
- 4.4-4.5 Circular lists
- **4.6-4.9 Linked stacks, queues, polynomials, equivalence classes, and sparse matrices**
- 4.10 Doubly linked lists
- 4.11 Generalized lists



Linked Stacks and Queues


- Stack

- Last in first out



- Queue

- First in first out






Linked Stack Operations

```
template <class T>
void LinkedStack <T>::Push(const T& e) {
    top = new ChainNode <T>(e, top);
}
```

```
template <class T>
void LinkStack <T>::Pop( )
{// Delete top node from the stack
    if (IsEmpty()) throw "Stack is empty. Cannot delete.";
    ChainNode <T> *delNode = top;
    top = top->link; // remove top node
    delete delNode; // free the node
}
```



Linked Queue Operations


```
template <class T>
void LinkedQueue <T>::Push(const T& e)
{
    if (IsEmpty( )) front = rear = new ChainNode(e,0);
    else rear = rear->link = new ChainNode(e,0);
    //attach node and update rear
}
```

```
template <class T>
void LinkedQueue <T>::Pop()
{ // Delete first element in queue
    if (IsEmpty()) throw "Queue is empty. Cannot delete.";
    ChainNode<T> *delNode = front;
    front = front->link; // remove first node from chain
    delete delNode;
}
```




Linked Polynomials


- We can have Polynomials that IS-IMPLEMENTED-IN-TERMS-OF Lists (instead of arrays)
- Definition
 - A data object of Type A IS-IMPLEMENTED-IN-TERMS-OF a data object of Type B if the Type B object is central to the implementation of the Type A object
 - This relationship is usually expressed by declaring the Type B object as a data member of the Type A object



Polynomial Classes


```
struct Term {  
    int coef;  
    int exp;  
    Term Set(int c, int e)  
    { coef=c; exp=e; return *this; }  
};  
class Polynomial{  
public:  
    // Polynomial operations  
private:  
    Chain<Term> poly;  
}
```





Adding Polynomials

$$\begin{array}{r} 3x^{14} + \quad \quad \quad 2x^8 \quad \quad \quad + 1 \\ + \quad 8x^{14} + -3x^{10} + \quad \quad \quad 10x^6 \\ \hline 11x^{14} + -3x^{10} + 2x^8 + 10x^6 + 1 \end{array}$$



```
Polynomial Polynomial::operator+(const Polynomial& b) const
{
    Term temp;
    Chain<Term>::ChainIterator ai = poly.begin(), bi = b.poly.begin();
    Polynomial c;
    while (ai && bi) {
        if (ai->exp == bi->exp) {
            int sum = ai->coef + bi->coef;
            if (sum) c.poly.InsertBack(temp.Set(sum, ai->exp));
            ai++; bi++;
        } else if (ai->exp < bi->exp) {
            c.poly.InsertBack(temp.Set(bi->coef, bi->exp));
            bi++;
        } else {
            c.poly.InsertBack(temp.Set(ai->coef, ai->exp));
            ai++;
        }
    }
    while (ai) {
        c.poly.InsertBack(temp.Set(ai->coef, ai->exp));
        ai++;
    }
    while (bi) {
        c.poly.InsertBack(temp.Set(bi->coef, bi->exp));
        bi++;
    }
    return c;
}
```




Outline


- 4.1-4.3 Basic singly linked lists and chains
- 4.4-4.5 Circular lists
- 4.6-4.9 Linked stacks, queues, polynomials,
equivalence classes, and sparse matrices
- 4.10 Doubly linked lists
- 4.11 Generalized lists



Equivalence Class Problem


- Integrated circuit (IC) fabrication involves exposing a silicon wafer using a series of masks (光罩)
- Each mask consists of several polygons that define metal lines
- Connected lines form power/signal net






Basic IC Fabrication Procedure

(Supplementary information)







The Fabrication of Integrated Circuits
<https://www.youtube.com/watch?v=35jWSQXku74>
<http://www.hitequest.com/Kiss/VLSI.htm>



Gallery

(Supplementary information)

Highly magnified view of copper tracks (insulating layers have been removed)



state of the
art has a 0.02
μm line pitch



Equivalence Class Problem

- We are given **polygons** and **overlap/equivalence pairs** (denoted by ' \equiv ') among polygons
- We want to partition the polygons into equivalence classes
- For example
 - Input: $0 \equiv 4, 3 \equiv 1, 6 \equiv 10, 8 \equiv 9, 7 \equiv 4, 6 \equiv 8, 3 \equiv 5, 2 \equiv 11$, and $11 \equiv 0$
 - Output: $\{0, 2, 4, 7, 11\}; \{1, 3, 5\}; \{6, 8, 9, 10\}$




Properties

- ' \equiv ' is reflexive
 - For any polygon x , $x \equiv x$
- ' \equiv ' is symmetric
 - For any two polygons x and y , if $x \equiv y$, then $y \equiv x$
- ' \equiv ' is transitive
 - For any three polygons x , y , and z , if $x \equiv y$ and $y \equiv z$, then $x \equiv z$



Algorithm

- Phase 1
 - Read and **store all equivalence pairs** (i, j)
- Phase 2
 - Begin at polygon 0 and find all pairs of the form $(0, j)$
 - 0 and these j 's are of the same class
 - Find all pairs of the form (j, k)
 - By transitivity, k is in the same class as 0 and j
 - Continue in this way until the entire equivalence class containing 0 has been found and output
 - Find an **object not yet output**, which is in a new equivalence class
 - Find and output the new equivalence class as before



Data Structure Design Decision


- For storing all equivalence pairs (i, j)

- n × n array

- e.g., `bool pairs[n][n]`

- Result in $\Theta(n^2)$ time complexity


- Chain representation



- n-element array, e.g., `bool out[n]`, is used for recording whether objects are output



Example



1. (Begin at 0) (Add 0 into a container, e.g., a stack)
2. (Get 0 from the container) Output 0 (Add 11 and 4 into the stack)
3. (Get 4 from the container) Output 4 (Add 7 into the stack)
4. (Get 7 from the container) Output 7 (No new objects are found)
5. (Get 11 from the container) Output 11 (Add 2 into the stack)
6. (Get 2 from the container) Output 2 (No new objects found)



Algorithm in C++


```
void Equivalence( )
{
    ifstream inFile("equiv.in", ios::in);
    if (!inFile) throw "Cannot open input file.";
    int i, j, n;
    inFile >> n; // number of objects
    // initialize first and out
    bool *out = new bool[n]; // an array of bool
    ENode **first = new ENode* [n]; // an array of pointers
    // use STL function fill to initialize
    fill (first, first + n, 0);
    fill (out, out + n, false);


    // Phase 1: input equivalence pairs
    inFile >> i >> j;
    while (inFile.good()) { //check end of file
        first[i] = new ENode (j, first[i])
        first[j] = new ENode (i, first[j])
        inFile >> i >> j;
    }
}
```

```

for (i = 0; i < n; i++) // Phase 2
    if (!out[i]) { // this object has not been output yet
        cout << endl << "A new class: " << i;
        out[i] = true; // mark the object
        stack<ENode> s; // initialize a stack
        ENode *x = first[i]; // obtain the ith list
        while (1) { // continue processing lists and the stack
            while (x) { // continue processing a list
                j = x->data;
                if (!out[j]) {
                    cout << ", " << j;
                    out[j] = true;
                    s.push(*x); // add *x into the stack
                } else{
                    x = x->link;
                }
            } // end of while(x)
            if (s.isEmpty()) break;
            x = s.top();
            s.pop(); // unstack
        } // end of while(1)
    } // end of if (!out[i])
}

```





Algorithm in C++ (cont'd)


```
for (i = 0; i < n; i++) // clean up Phase-1-created objected
    while (first[i]) {
        ENode *delnode = first[i];
        first[i] = delnode->link;
        delete delnode;
    }
delete [] first;
delete [] out;
```

- Time complexity = $O(m+n)$
 - Initialization of `first[]` and `out[]` takes $O(n)$ time
 - where n is the number of objects
 - Processing of each input pair in phase takes $O(m)$
 - where m is the number of input pairs
 - The **for** loop takes $O(n)$ time
 - Evaluating of the $2m$ pairs takes $O(m)$ time




Outline

- 4.1-4.3 Basic singly linked lists and chains
- 4.4-4.5 Circular lists
- **4.6-4.9** Linked stacks, queues, polynomials, equivalence classes, and **sparse matrices**
- 4.10 Doubly linked lists
- 4.11 Generalized lists




Sparse Matrices

- Array-based representation (we have learned this before)
 - Row access is easy, but column access is difficult
- Linked representation
 - Easy access both by row and column
- Node design (head field will not be shown later)





Linked Sparse Matrix








Figure Explanations





Sparse Matrix Definition

```
struct Triple{  
    int row, col, value;  
};  
  
class Matrix; // forward declaration  
  
class MatrixNode {  
friend class Matrix;  
friend istream& operator>>(istream&, Matrix&);  
// for reading in a matrix  
private:  
    MatrixNode *down , *right;  
    bool head;  
    union {  
        MatrixNode *next;  
        Triple triple;  
    };  
    MatrixNode(bool, Triple*); // constructor  
}
```

*// union allow multiple objects to
// overlap with one another.
// Programmers are responsible to
// take care the use of them.*



Sparse Matrix Definition

```
MatrixNode::MatrixNode(bool b, Triple *t) // constructor
{
    head = b;
    if (b) { // row/column header node
        right = down = this;
    }else{
        triple = *t; // element node
    }
}


class Matrix{
friend istream& operator>>(istream&, Matrix&);
public:
    ~Matrix(); // destructor
private:
    MatrixNode *headnode;
};
```



Sparse Matrix Input

- Overloading the `>>` operator makes sparse matrix more like **built-in types**

```
int i, j, k;  
cin >> i >> j >> k;  
Matrix mi, mj, mk;  
cin >> mi >> mj >> mk;
```






Sparse Matrix Input

```
istream& operator>>(istream& is, Matrix& matrix)
{// Read in a maxtix and set up its linked representation
Triple s;
is >> s.row >> s.col >> s.value; // matrix dimensions
int p = max(s.row, s.col);
// set up header node for list of header nodes
matrix.headnode = new MatrixNode(false, &s);
if (p == 0) {
    matrix.headnode->right = matrix.headnode;
    return is; // for supporting "cin >> mi >> mj;";
}
// at least one row or column
MatrixNode **head = new MatrixNode* [p];
for (int i = 0; i < p; i++)
    head[i] = new MatrixNode(true, 0);

// please continue on the next page
```



Sparse Matrix Input

```
int currentRow = 0;
int MatrixNode *last = head[0]; // last node in current row
for (i = 0; i < s.value; i++) // input triples
{
    Triple t;
    is >> t.row >> t.col >> t.value;
    if (t.row > currentRow) { // end of current row
        last->right = head[currentRow]; // close current row
        currentRow = t.row;
        last = head[currentRow];
    } // end of if

    last = last->right = new MatrixNode(false, &t);
    // link new node into row list

    head[t.col]->next = head[t.col]->next->down = last;
    // link into column list
} // end of for
// please continue on the next page
```




Sparse Matrix Input

```
last->right = head[currentRow]; // close last row
for (i = 0; i < s.col; i++)
    head[i]->next->down = head[i] // close all column lists

// link the header nodes together
for (i = 0; i < p; i++)
    head[i]->next = head[i + 1];
head[p-1]->next = matrix.headnode;
matrix.headnode->right = head[0];

delete [] head;
return is;
}
```



Sparse Matrix Deletion

```
Matrix::~Matrix()
{ // Return all nodes to the av list, which is a chain linked
 // via the right field.
 // av is a static variable pointing to the first of the av list.
 if (!headnode)
     return; // no nodes to delete
 MatrixNode *x = headnode->right;

 headnode->right = av;
 av = headnode; // return headnode

 while (x != headnode) { // return nodes by rows
     MatrixNode *y = x->right;
     x->right = av;
     av = y;
     x = x->next; // next row
 }
 headnode = 0;
}
```




Outline

- 4.1-4.3 Basic singly linked lists and chains
- 4.4-4.5 Circular lists
- 4.6-4.9 Linked stacks, queues, polynomials, equivalence classes, and sparse matrices
- **4.10 Doubly linked lists**
- 4.11 Generalized lists




Doubly Linking vs. Singly Linking

- Doubly linked
 - Each node contain pointers to the both direction
 - Traversal can be performed **in both direction**




- Singly linked
 - Traversal can only be performed **in one direction**






Circular, Doubly Linked Lists with Header

- Empty list



- Non-empty list





Doubly Linked List Definition

```
class DblList; //forward declaration

class DblListNode {
friend class DblList;
private:
    int data;
    DblListNode * left, * right;
};


class DblList {
public:
    // List manipulation operations
    .
    .
private:
    DblListNode *head; // points to header node
};
```

Please note the syntax for
declaring two pointers a line



Insertion Operation


```
void DblList :: Insert(DblListNode *p, DblListNode *x)
{ // insert node p to the right of node x
    p->left = x;          1
    p->right = x->right;  2
    x->right->left = p;  3
    x->right = p;         4
}
```





Deletion Operation

```
void DblList :: Delete(DblListNode *x)
{
    if (x == head)
        throw "Deletion of header node not permitted";
    else {
        x->left->right = x->right; ①
        x->right->left = x->left; ②
        delete x;
    }
}
```





Outline

- 4.1-4.3 Basic singly linked lists and chains
- 4.4-4.5 Circular lists
- 4.6-4.9 Linked stacks, queues, polynomials, equivalence classes, and sparse matrices
- 4.10 Doubly linked lists
- **4.11 Generalized lists**



Generalized Lists

- Generalized list
 - Finite sequence of $n \geq 0$ elements, (a_0, \dots, a_n) , where a_i is either an atom or a list
- Head
 - a_0
- Tail
 - (a_1, \dots, a_n)



Exampling Generalized Lists

- **A = ()**
 - Empty (also referred to as **null**) list
 - Length is zero
- **B = (a, (b, c))**
 - Length is two
 - First element is the atom a
 - Second element is the list (b, c)
- **C = (B, B, ())**
 - Length is three
 - First two elements are the list B
 - Third element is the empty list
- **D = (a, D)**
 - Recursive definition
 - Corresponds to the infinite list (a, (a, (a, ...)))



Exampling Generalized Lists

- $A = ()$
 - $B = (a, (b, c))$
 - $C = (B, B, ())$
 - $D = (a, D)$
-
- $\text{head}(B) = a$
 - $\text{tail}(B) = ((b, c))$
 - $\text{head}(\text{tail}(B)) = (b, c)$
 - $\text{tail}(\text{tail}(B)) = ()$
-
- $\text{head}(C) = B$
 - $\text{tail}(C) = (B, ())$



Generalized-List Polynomials

- Example

- $x^{10}y^3z^2 + 2x^8y^3z^2 + 3x^8y^2z^2 + x^4y^4z + 6x^3y^4z + 2yz$

- Factorizing out variables

- $x^{10}y^3z^2 + 2x^8y^3z^2 + 3x^8y^2z^2 + x^4y^4z + 6x^3y^4z + 2yz$

$$= (x^{10}y^3 + 2x^8y^3 + 3x^8y^2)z^2 + (x^4y^4 + 6x^3y^4 + 2y)z$$

$$= \underline{(x^{10} + 2x^8)y^3 + 3x^8y^2}z^2 + \underline{((x^4 + 6x^3)y^4 + 2y)}z$$


||

$$\underline{C(x, y)z^2} + \underline{D(x, y)z}$$

//

\\

$$\underline{E(x)y^3 + F(x)y^2} \quad \underline{G(x)y^4 + G(x)y}$$



Generalized-List Polynomials

- $((x^{10} + 2x^8)y^3 + 3x^8y^2)z^2 + ((x^4 + 6x^3)y^4 + 2y)z$
- Three types of information
 - Factored-out variable e.g., 'z'
 - Exponent of the factored variable and a link to the associated sub-polynomial e.g., 2
 $(x^{10} + 2x^8)y^3 + 3x^8y^2$
 - Coefficient of each term e.g., 1
- Node structure for storing the information

type of the node
variable name / link to sub-polynomial / coefficient
exponent (optional)
link to the next node



Generalized-List Polynomials

$$\bullet ((x^{10} + 2x^8)y^3 + 3x^8y^2)z^2 + ((x^4 + 6x^3)y^4 + 2y)z$$


$$3x^8 \quad \boxed{x \ 0} \rightarrow \boxed{3 \ 8 \ 0}$$

$$x^{10} + 2x^8 \quad \boxed{x \ 0} \rightarrow \boxed{1 \ 10} \rightarrow \boxed{2 \ 8 \ 0}$$



Generalized-List Polynomials


$$\bullet ((x^{10} + 2x^8)y^3 + 3x^8y^2)z^2 + ((x^4 + 6x^3)y^4 + 2y)z$$





Generalized-List Polynomials


$$\bullet ((x^{10} + 2x^8)y^3 + 3x^8y^2)z^2 + ((x^4 + 6x^3)y^4 + 2y)z$$





Generalized-List Polynomials

$$\bullet ((x^{10} + 2x^8)y^3 + 3x^8y^2)z^2 + ((x^4 + 6x^3)y^4 + 2y)z$$






Node Definition

```
enum NodeType{var, ptr, no}; // var=0, ptr=1, no=2
class PolyNode
{
    NodeType type;

    char name;
    PolyNode* sub;
    int coef;

    int exp;
    PolyNode* next; // link to next node
}
```

type of the node
variable name
link to sub-polynomial
coefficient
exponent (optional)
link to the next node



Node Definition

```
enum NodeType{var, ptr, no}; // var=0, ptr=1, no=2
class PolyNode
{
    NodeType type;
    union{
        char name;
        PolyNode* sub;
        int coef;
    }
    int exp;
    PolyNode* next; // link to next node
}
```

// three variables overlap in memory

type of the node
name / sub / coef
exponent (optional)
link to the next node

reduced node size




Generalized Lists

- Node structure



- $A = ()$
- $A' = (())$
- $B = (a, (b, c))$
- $C = (B, B, ())$
- $D = (a, D)$





Generalized List

```
template <class T> class GenList; // forward declaration
template <class T>
class GenListNode{
friend class GenList <T>;
private:
    GenListNode<T>* next;
    bool tag;
    union {
        T data;
        GenListNode<T>* down;
    }
}
template <class T>
class GenList{
public:
    // List manipulation operations
private:
    GenListNode<T>* first;
}
```



Copying a List

```
// Driver
void GenList<T>::Copy(const GenList<T>& l)
{ // make a copy of l
    first = Copy (l.first);
}

// Workhorse
GenListNode<T>* GenList<T>::Copy(GenListNode<T>* p)
{// Copy the nonrecursive list with no shared sublists
    GenListNode<T>*q = 0;
    if (p) {
        q = new GenListNode<T>;
        q->tag = p->tag;
        if (p->tag) q->down = Copy (p->down);
        else q->data = p->data;
        q->next = Copy(p->next);
    }
    return q;
}
```



Testing Equality for Two Lists

```
// Driver
template<class T>
bool operator == (const GenList<T>& l) const
{// *this and l are non-recursive lists
 // return true iff the two lists are identical
    return Equal (first, l.first);
}

// Workhorse
bool Equal(GenListNode<T>*s, GenListNode<T>*t)
{
    if ((!s) && (!t)) return true;
    if (s && t && (s->tag == t->tag))
        if (s->tag)
            return Equal(s->down, t->down)&&Equal(s->next, t->next);
        else
            return (s->data == t->data)&&Equal(s->next, t->next);
    return false;
}
```




Computing the List Depth


```
// Driver // Depth ≡ max degree of nested sublists
template <class T>
int GenList<T>::Depth()
{ // Compute the depth of a non-recursive list
    return Depth(first);
}
// Workhorse
template <class T>
int GenList::Depth(GenListNode<T>* s)
{
    if (!s) return 0; // empty list
    GenListNode<T>* current = s;
    int m=0; // initial minimum value
    while (current) {
        if (current->tag) m = max(m, Depth(current->down));
        current = current->next;
    } // m is the max depth among sublists
    return m+1;
}
```



Computing the List Depth




```
template <class T>
int GenList::Depth(GenListNode<T>* s)
{
    if (!s) return 0; // empty list
    GenListNode<T>* current = s;
    int m=0;
    while (current) {
        if (current->tag) m = max(m, Depth(current->down));
        current = current->next;
    } // m is the max depth among sublists (m=0 if no sublists exist)
    return m+1; // increments m for the current list
}
```



Adding a Node or Deleting a Lists


- Design issues
 - Adding or deleting node at the front of a list can affect the *down* fields of other lists
 - e.g., adding an 'x' in front of 'a' in **B**
 - We normally do not know these affected fields
 - Determining whether list nodes need to be freed
 - e.g., the node 'a' needs to be kept (if other lists require it) even if **B.first** no longer points to it






Headers and Reference Counts

- Each list/sublist equips a header
 - Adding and deleting node at the front of the list does not affect other lists
- Headers serve the reference point of a list
- Header tracks the reference count, the number of pointers pointing to the lists
 - List nodes with no reference to them require being freed



Headers and Reference Counts

- $A = ()$
- $B = (a, (b, c))$
- $C = (B, B, ())$
- $D = (a, D)$





Deleting Generalized Lists

```
// Driver
template <class T>
GenList<T>::~GenList() // Destructor
{ // Each header node has a reference count
    if (first){
        Delete(first);
        first = 0;
    }
}
// Workhorse
void GenList<T>::Delete(GenListNode<T>* x)
{
    x->ref--; // decrement reference count of header node
    if (!x->ref){
        GenListNode<T> *y = x;
        while (y->next) // y traverses top level of x
        { y = y->next; if (y has down link) Delete(y->down); }
        y->next = av; // attach top-level nodes to av list
        av = x;
    }
}
```