Lab 9: Keyboard (Calculator)

Objective

✓ Implement keyboard function.


Prerequisite

- ✓ Fundamentals of logic gates.
- ✓ Logic modeling in Verilog HDL.
- ✓ Keyboard control procedure

Experiments

按下去數字會一直顯示

- 1 Implement Key Board
 - 1.1 Press 0/1/2/3/4/5/6/7/8/9 and show them in the seven-segment display. When a new number is pressed, the previous number is refreshed and over written.
 - 1.2 Press a/s/m (addition/subtraction/multiplication) and show them in the seven-segment display as your own defined A/S/M pattern. When you press "Enter", refresh (turn off) the seven-segment display.
- 2 Implement a single digit decimal adder using the keyboard as the input and display the results on the 14-segment display (The first two digit are the addend/augend, and the last two digits are the sum).
- Implement a two-digit decimal adder/subtractor/multiplier using the right-hand-side keyboard (inside the red block). You don't need to show all inputs and outputs at the same time in the 7-segment display. You just need to show inputs when they are pressed and show the results after "Enter" is pressed.



- 4 Implement the "Caps" control in the keyboard. When you press A-Z and a-z in the keyboard, the ASCII code of the pressed key (letter) is shown on 7-bit LEDs.
 - 4.1 Press "Caps Lock" key to change the status of capital/lower case on the keyboard. Use a led to indicate the status of capital/lowercase in the keyboard and show the ASSCII code of the pressed key one 7-bit LEDS.
 - 4.2 Implement the combinational keys. When you press "Shift" and the letter keys at the

same time. The 7-bit LEDs will show the ASCII code of the uppercase/lowercase of the pressed letter when the "Caps Lock" is at the lowercase/uppercase status.

```
Dec Hx Oct Char
                                      Dec Hx Oct Html Chr Dec Hx Oct Html Chr Dec Hx Oct Html Chr
 0 0 000 NUL (null)
                                       32 20 040 @#32; Space
                                                             64 40 100 @#64; 0
                                                                                96 60 140 @#96;
    1 001 SOH (start of heading)
                                       33 21 041 4#33; !
                                                             65 41 101 A A
                                                                                97 61 141 @#97;
                                       34 22 042 4#34;
                                                             66 42 102 B B
                                                                                98 62 142 6#98;
    2 002 STX (start of text)
    3 003 ETX
              (end of text)
                                       35 23 043 4#35; #
                                                             67 43 103 @#67;
                                                                                99 63 143 4#99;
    4 004 E0T
              (end of transmission)
                                       36 24 044 $ $
                                                             68 44 104 4#68;
                                                                               |100 64 144 d d
                                                                            E
                                                                               101 65 145 e e
    5 005 ENO
              (enquiry)
                                       37 25 045 % 🕏
                                                             69 45 105 4#69;
    6 006 ACK
                                       38 26 046 4#38;
                                                             70 46 106 4#70;
                                                                               102 66 146 f
              (acknowledge)
                                                                               103 67 147 @#103; g
    7 007 BEL
              (bell)
                                       39 27 047 4#39;
                                                             71 47 107 6#71;
    8 010 BS
              (backspace)
                                       40 28 050 6#40;
                                                             72 48 110 @#72;
                                                                               104 68 150 @#104; h
                                                             73 49 111 6#73;
                                                                               105 69 151 i <mark>i</mark>
 9
    9 011 TAB
              (horizontal tab)
                                       41 29 051 )
10
    A 012 LF
              (NL line feed, new line)
                                       42 2A 052 @#42;
                                                             74 4A 112 @#74;
                                                                               106 6A 152
                                                                                          j
                                       43 2B 053 +
                                                                               107 6B 153 k
11
    B 013 VT
              (vertical tab)
                                                             75 4B 113 6#75;
    C 014 FF
              (NP form feed, new page)
                                       44 2C 054 @#44;
                                                             76 4C 114 L
                                                                               108 6C 154 @#108; l
12
                                       45 2D 055 -
                                                             77 4D 115 M M
13
   D 015 CR
              (carriage return)
                                                                               |109 6D 155 m 🎹
14
    E 016 S0
              (shift out)
                                       46 2E 056 .
                                                             78 4E 116 @#78;
                                                                               110 6E 156 n n
                                                                               111 6F 157 o º
                                       47 2F 057 /
1.5
    F 017 SI
              (shift in)
                                                             79 4F 117 @#79; 0
16 10 020 DLE
              (data link escape)
                                       48 30 060 4#48; 0
                                                             80 50 120 P P
                                                                               112 70 160 p p
                                                             81 51 121 Q 0
17 11 021 DC1
              (device control 1)
                                       49 31 061 4#49; 1
                                                                               |113 71 161 &#ll3; <mark>q</mark>
                                       50 32 062 4#50;
                                                             82 52 122 6#82;
                                                                               114 72 162 @#114;
18 12 022 DC2
              (device control 2)
                                                                               115 73 163 @#115;
19 13 023 DC3
              (device control 3)
                                       51 33 063 3 3
                                                             83 53 123 4#83;
20 14 024 DC4
                                       52 34 064 4#52; 4
                                                             84 54 124 @#84;
                                                                               116 74 164 t t
              (device control 4)
21 15 025 NAK (negative acknowledge)
                                       53 35 065 5 5
                                                             85 55 125 @#85;
                                                                               117 75 165 u <mark>u</mark>
22 16 026 SYN
                                       54 36 066 6 6
                                                             86 56 126 @#86;
                                                                                   76 166 @#118;
              (synchronous idle)
                                                                               118
                                       55 37 067 4#55; 7
23 17 027 ETB
              (end of trans. block)
                                                             87 57 127 4#87;
                                                                               119
                                                                                   77 167 w ₩
24 18 030 CAN
              (cancel)
                                       56 38 070 4#56; 8
                                                             88 58 130 4#88;
                                                                               120 78 170 x ×
25 19 031 EM
              (end of medium)
                                       57 39 071 4#57; 9
                                                             89 59 131 4#89;
                                                                               |121 79 171 y Y
                                       58 3A 072 @#58;
                                                             90 5A 132 @#90;
                                                                               122 7A 172 @#122;
26 1A 032 SUB
              (substitute)
27 1B 033 ESC
              (escape)
                                       59 3B 073 &#59; ;
                                                             91 5B 133 [
                                                                               123 7B 173 {
28 1C 034 FS
                                       60 3C 074 < <
                                                             92 5C 134 @#92;
                                                                               124 7C 174 @#124;
              (file separator)
29 1D 035 GS
              (group separator)
                                       61 3D 075 = =
                                                             93 5D 135 6#93;
                                                                               125 7D 175 }
                                       62 3E 076 > >
                                                             94 5E 136 @#94;
                                                                               126 7E 176 @#126;
30 1E 036 RS
              (record separator)
                                                                              127 7F 177  DEL
31 1F 037 US
              (unit separator)
                                       63 3F 077 ? ?
                                                            95 5F 137 @#95;
```

© Ma, Hsi-Pin, Lab for Reliable Computing (LaRC), EE, NTHU.

Source: www.LookupTables.com